

# Bullet IP Camera

2 Mega Pixel Bullet

**EE2MPVF**



## FEATURES

**H.264**

**2MP  
1080P**

1/2.8" SONY Starvis Back-illuminated CMOS Sensor

H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG

2.7-13.5mm Motorized Lens

Onvif Compliant

## EE2MPVF

### 2MP Bullet IP | EE2MPVF

v1.2-5.23

Camera	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Resolution	2MP 1080P
Effective Pixels	1945(H)*1097(V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	≥52dB
Scanning System	Progressive
Lens	
Focus Length	2.7-13.5mm
Focus Control	1HD,1 VGA, 1CVBS
Lens Type	Analog/AHD/CVI/TVI 2.0/Network
Pixels	2MP
Night Vision	
Infrared LED	42μ x 6PCS
Infrared Distance	60M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP,HTTP,HTTPS,DHCP,RTP,RTSP,RTCP,NTP
Onvif	Support ONVIF 2.4
Streamer	v4.1
POE	Optional, Support IEEE 802.3af
Main Stream 1	1920*1080@30fps
Main Stream 2	1280*720@30fps
Camera Features	
Day/Night	Color/ B&W (IR-CUT )
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
Defog mode	Support
WDR	Support
Motion Detection	Support
General	
Housing	Metal, IP66
IR Cut Filter	Yes
Operation Temperature	-20°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 1150mA
Dimension	312(W) x 133(H) x102(D)mm
Weight	1800g

\*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.