


IOT SERVERDIGITAL VIDEO HOST

EEN16HS-B





FEATURES

High performance cloud technology DVR





Pentabrid(AHD+TVI+CVI+Analog+ IP) DVR with NVR functionality and IP camera support.

HDMI / VGA / Video simultaneous video output

Technical Specifications

EEN16HS-B



IoT-Server | EEN16HS-B

v1.2-5.23

System	
Operating System	Linux (Ubuntu 16.04 LTS Server or higher)
Video	
Input	Analog: 16*1080N Network:16*(4K)
Signal Type	Analog/AHD/CVI/TVI 2.0/Network
Audio	
Input	2 Channel, RCA
Output	1 Channel, RCA
Video Output	
Encoding	16 Channels H.264 + Secondary Stream 4 Channels 4K
Network	
Interface	1 RJ45 10M/100M Adaptive Ethernet Interface
Network Functions	HTTP, RTSP, IPv4,IPv6, NTP, FTP, UPNP
Secondary Stream	CIF(1~12fps) on Analogue Input 1080N on Digital Input
General	
Power Consumption	DC 12V ≤6W (Without Hard Disk)
Working Environ	-10~55°C/10~90%

^{*}Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.