

PTZ Analogue

2 MP Bullet PTZ

EEPTZ2MA



FEATURES

UTC

2MP

10x

1/2.9" SONY Low Illumination 2.1MP CMOS Sensor

Pan/Tilt/Zoom Bullet

5.1mm-51mm

10X Optical Zoom

PTZ IP Bullet | EEPTZ2MA

v1.2-8.23

| Camera | |
|---------------------------|--|
| Image Sensor | 1/2.9" SONY Low Illumination 2.1MP CMOS Sensor |
| Resolution | 2MP |
| S/N Ratio | ≥50dB |
| PTZ | |
| Horizontal Rotation Speed | 30°/S |
| Horizontal Rotation Range | 0°~200° |
| Tilt Rotation Range | -45°~40° |
| Tilt Rotation Speed | 25°/S |
| Auto Flip | No Support |
| Ratio Speed | No Support |
| 360 Scan | No Support |
| A-B Scan | Support |
| Preset Points | 220 |
| Guard Tours | 3 Groups |
| Guard Points | Max 16 points |
| Lens | |
| Focus Length | 5.1mm-51mm |
| Focus Control | 10X Optical Zoom |
| Night Vision | |
| Infrared LED | 4PCS Array IR LEDES + 2PCS Laser Lamp |
| Infrared Distance | 100M |
| Auto Control IR LED | PWM |
| Communication | |
| Comm Protocol | UTC |
| Comm Interface | Coaxial Cable |
| RS485 | Support |
| General | |
| Housing | Metal, IP66 |
| Operation Temperature | Indoor: 0°~ +40° Outdoor: -40°~ +60° |
| Operating Humidity | ≤90% Non Condensing |
| Heater & Blower | Auto temperature control |
| Power | DC12V/3A |
| Lightning Protection | Transient voltage 6000V |
| Dimension | 39.6x19.6x16(cm) |
| Weight | 3Kgs |

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.