

# 360 IP Camera

12 Mega Pixel

## EE12MP360-S



## FEATURES

**12MP**

**H.264**

**360**

1/1.7" SONY Low Illumination CMOS Sensor

H.264/H.265/MJPEG/AVI

PoE Support IEEE 802.3af

Onvif Compliant

## EE12MP360-S

### 360 Fisheye | EE12MP360-S

v1.2-8.17

Camera	
Image Sensor	1/1.7" SONY Low Illumination CMOS Sensor
Resolution	12MP
Effective Pixels	4072 (H) × 3046 (V)
Compression	H.264/H.265/MJPEG/AVI
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	≥52dB
Scanning System	Progressive
Lens	
Focus Length	Board Lens 1.77mm/F2.4 (Fisheye)
Focus Control	Fixed
Lens Type	Fixed
Pixels	12MP
Night Vision	
Infrared LED	42μx 3PCS
Infrared Distance	20M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP,HTTP,DHCP,RTP,RTSP,RTCP,NTP
Onvif	Support ONVIF 2.4
Streamer	V4.1
POE	Internal POE, Support IEEE 802.3af
Main Stream 1	4000*3000@20fps
Main Stream 2	3000*3000@30fps
Camera Features	
Day/Night	Color/ B&W (IR cut filter with auto switch )
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
Defog mode	Support
WDR	Support
Motion Detection	Support
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean,Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands,Ukrainian
Audio	2-way audio(3.5mm audio interface)
Alarm	1channel Input/Ouput
SD Card Support	Support 64G Micro SD
General	
Housing	Body: Metal, Bracket: Plastic
IR Cut Filter	Yes
Operation Temperature	-20°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 950mA
Dimension	φ120 x 49(H) mm
Weight	500g
<b>#Software license compatibility codes: FW-STRRSPxx, ES-STRTSPxx, ES-STRMFULLxx</b>	

\*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.