

PTZ Analogue

2 MP Bullet PTZ

EEPTZ2MA-S



FEATURES

UTC

2MP

10x

1/2.9" SONY Low Illumination 2.1MP CMOS Sensor

Pan/Tilt/Zoom Bullet

5.1mm-51mm

10X Optical Zoom

EEPTZ2MA-S

PTZ IP Bullet | EEPTZ2MA-S

v1.2-8.23

Camera	
Image Sensor	1/2.9" SONY Low Illumination 2.1MP CMOS Sensor
Resolution	2MP
S/N Ratio	≥50dB
PTZ	
Horizontal Rotation Speed	30°/S
Horizontal Rotation Range	0°~200°
Tilt Rotation Range	-45°~40°
Tilt Rotation Speed	25°/S
Auto Flip	No Support
Ratio Speed	No Support
360 Scan	No Support
A-B Scan	Support
Preset Points	220
Guard Tours	3 Groups
Guard Points	Max 16 points
Lens	
Focus Length	5.1mm-51mm
Focus Control	10X Optical Zoom
Night Vision	
Infrared LED	4PCS Array IR LEDS + 2PCS Laser Lamp
Infrared Distance	100M
Auto Control IR LED	PWM
Communication	
Comm Protocol	UTC
Comm Interface	Coaxial Cable
RS485	Support
General	
Housing	Metal, IP66
Operation Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤90% Non Condensing
Heater & Blower	Auto temperature control
Power	DC12V/3A
Lightning Protection	Transient voltage 6000V
Dimension	39.6x19.6x16(cm)
Weight	3Kgs
# Software license compatibility codes: FW-STRRSPxx ; ES-STRTSPxx, ES-STRMFULLxx	

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.