

Video Compressor 64CH GPU

EEVEG64



FEATURES

ARM Cortex A17 Quad-core Processor

H265/H264/H265+/H264+

Streamer GPU

64CH Inputs
Gigabit

Linux Embedded

Technical Specifications

EEVEG64



64CH GPU Compressor | EEVEG64

v1.8.21

English, Spanish, Portuguese USB Interface 1 USB 2.0 Interfaces, 1 USB 3.0 Interface 1 USB 240 VAC, 50 to 60 Hz		V1.0.21	
Streamer Dedicated GPU Streamer Streamer Support Storage Storage	System		
Streamer Dedicated GPU Video	Main Processor	ARM Cortex A17 Quad-core Processor	
Video	Operating System	Embedded Linux	
Input	GPU	Streamer Dedicated GPU	
Name	Video		
Input	Input		
Output 1 Port RCA(Linear, 1kΩ) Audio Bit Rate 64kbs Audio Compression G.711 Network Interface 1 RJ45 10M/100/1000M Adaptive Ethernet Interface Incoming Bandwidth 300MB Netowrk Funcions TCP/CP, HTTP, RTP, RTSP, RTCP, Streamer Support Version 3.5 Storage Interface Type 8 SATA Interface Capacity Up to 48TB capacity eSATA 1 eSATA Interface General Language English, Spanish, Portuguese USB Interface 1 USB 2.0 Interfaces ,1 USB 3.0 Interface Power Supply 100 to 240 VAC, 50 to 60 Hz	Audio		
Audio Bit Rate Audio Compression Setwork	Input	1 Port RCA	
Network Interface 1 RJ45 10M/100/1000M Adaptive Ethernet Interface Incoming Bandwidth 300MB Netowrk Funcions TCP/CP, HTTP, RTP, RTSP, RTCP, Streamer Support Version 3.5 Storage Interface Type 8 SATA Interface Capacity Up to 48TB capacity eSATA 1 eSATA Interface General Language English, Spanish, Portuguese USB Interface 1 USB 2.0 Interfaces ,1 USB 3.0 Interface Power Supply 100 to 240 VAC, 50 to 60 Hz	Output	1 Port RCA(Linear, 1kΩ)	
Network Interface	Audio Bit Rate	64kbs	
Interface 1 RJ45 10M/100/1000M Adaptive Ethernet Interface Incoming Bandwidth 300MB Netowrk Funcions TCP/CP, HTTP, RTP, RTSP, RTCP, Streamer Support Version 3.5 Storage Interface Type 8 SATA Interface Capacity Up to 48TB capacity eSATA 1 eSATA Interface General Language English, Spanish, Portuguese USB Interface 1 USB 2.0 Interfaces, 1 USB 3.0 Interface Power Supply 100 to 240 VAC, 50 to 60 Hz	Audio Compression	G.711	
Incoming Bandwidth 300MB Netowrk Funcions TCP/CP, HTTP, RTP, RTSP, RTCP, Streamer Support Version 3.5 Storage Interface Type 8 SATA Interface Capacity Up to 48TB capacity eSATA 1 eSATA Interface General Language English, Spanish, Portuguese USB Interface 1 USB 2.0 Interfaces ,1 USB 3.0 Interface Power Supply 100 to 240 VAC, 50 to 60 Hz	Network		
Netowrk Funcions TCP/CP, HTTP, RTP, RTSP, RTCP, Streamer Support Storage Interface Type 8 SATA Interface Capacity Up to 48TB capacity eSATA 1 eSATA Interface General Language English, Spanish, Portuguese USB Interface 1 USB 2.0 Interfaces, 1 USB 3.0 Interface Power Supply 100 to 240 VAC, 50 to 60 Hz	Interface	1 RJ45 10M/100/1000M Adaptive Ethernet Interface	
Streamer Support Storage Interface Type 8 SATA Interface Capacity Up to 48TB capacity eSATA 1 eSATA Interface General Language English, Spanish, Portuguese USB Interface 1 USB 2.0 Interfaces, 1 USB 3.0 Interface Power Supply Version 3.5 Storage 8 SATA Interface Up to 48TB capacity 1 eSATA Interface General Language Interface 1 USB 2.0 Interfaces, 1 USB 3.0 Interface	Incoming Bandwidth	300MB	
Storage Interface Type 8 SATA Interface Capacity Up to 48TB capacity eSATA 1 eSATA Interface General Language English, Spanish, Portuguese USB Interface 1 USB 2.0 Interfaces ,1 USB 3.0 Interface Power Supply 100 to 240 VAC, 50 to 60 Hz	Netowrk Funcions	TCP/CP, HTTP, RTP, RTSP, RTCP,	
Interface Type 8 SATA Interface Capacity Up to 48TB capacity eSATA 1 eSATA Interface General Language English, Spanish, Portuguese USB Interface 1 USB 2.0 Interfaces ,1 USB 3.0 Interface Power Supply 100 to 240 VAC, 50 to 60 Hz	Streamer Support	Version 3.5	
Capacity eSATA 1 eSATA Interface General Language English, Spanish, Portuguese USB Interface 1 USB 2.0 Interfaces, 1 USB 3.0 Interface Power Supply 100 to 240 VAC, 50 to 60 Hz	Storage		
English, Spanish, Portuguese USB Interface 1 USB 2.0 Interfaces, 1 USB 3.0 Interface 1 USB 240 VAC, 50 to 60 Hz	Interface Type	8 SATA Interface	
General Language English, Spanish, Portuguese USB Interface 1 USB 2.0 Interfaces ,1 USB 3.0 Interface Power Supply 100 to 240 VAC, 50 to 60 Hz	Capacity	Up to 48TB capacity	
LanguageEnglish, Spanish, PortugueseUSB Interface1 USB 2.0 Interfaces ,1 USB 3.0 InterfacePower Supply100 to 240 VAC, 50 to 60 Hz	eSATA	1 eSATA Interface	
USB Interface1 USB 2.0 Interfaces ,1 USB 3.0 InterfacePower Supply100 to 240 VAC, 50 to 60 Hz	General		
Power Supply 100 to 240 VAC, 50 to 60 Hz	Language	English, Spanish, Portuguese	
	USB Interface	1 USB 2.0 Interfaces ,1 USB 3.0 Interface	
	Power Supply	100 to 240 VAC, 50 to 60 Hz	
Working Environment -10~55/10~90%	Working Environment	-10~55/10~90%	
Dimension 2U, 440mm×450mm×95mm	Dimension	2U, 440mm×450mm×95mm	
Weight 9.8Kg□without HDD□	Weight	9.8Kg□without HDD□	

^{*}Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.