

# PTZ IP CAMERA

2 MP Bullet PTZ

**EEPTZ2MIP**



## FEATURES

**H.265**

**2MP**

**10x**

1/2.9" SONY Low Illumination 2.1MP CMOS Sensor

Pan/Tilt/Zoom Bullet

5.1mm-51mm

10X Optical Zoom

### PTZ IP Bullet | EEPTZ2MIP

v1.2-8.23

Camera	
Image Sensor	1/2.9" SONY Low Illumination 2.1MP CMOS Sensor
Resolution	2MP
Compression	H.264/H.265
S/N Ratio	≥50dB
PTZ	
Horizontal Rotation Speed	30°/S
Horizontal Rotation Range	0°~200°
Tilt Rotation Range	-45°~40°
Tilt Rotation Speed	25°/S
Auto Flip	No Support
Ratio Speed	No Support
360 Scan	No Support
A-B Scan	Support
Preset Points	220
Guard Tours	3 Groups
Guard Points	Max 16 points
Lens	
Focus Length	5.1mm-51mm
Focus Control	10X Optical Zoom
Night Vision	
Infrared LED	4PCS Array IR LEDES + 2PCS Laser Lamp
Infrared Distance	100M
Auto Control IR LED	PWM
Network	
Ethernet	Built-in RJ45 network interface,support 10M/100M IP DATA
Protocol	TCP/IP,HTTP,HTTPS,DHCP,RTP,RTSP,RTCP,NTP
Streamer	v4.1
Main Stream	1080P@30fps
Sub Stream	640*480/480*360
MJPEG	1280*720
General	
Housing	Metal, IP66
Operation Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤90% Non Condensing
Heater & Blower	Auto temperature control
Power	DC12V/3A
Lightning Protection	Transient voltage 6000V
Dimension	39.6x19.6x16(cm)
Weight	3Kgs

\*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.