

# PTZ IP CAMERA

2 Mega Pixel PTZ

**EEPTZ2MP-22X**



## FEATURES

1/2.9" SONY Low Illumination 2.1MP CMOS Sensor

**H.264**

**2MP  
1080P**

**22X**

H.264 2MP Pan/Tilt/Zoom

3.9mm-85.5mm

22X Optical Zoom

## EEPTZ2MP-22X

### PTZ IP Camera | EEPTZ2MP22X

v1.2-5.23

Camera	
Image Sensor	1/2.9" SONY Low Illumination 2.1MP CMOS Sensor
Resolution	2MP 1080P
Effective Pixels	1945(H)*1097(V)
Compression	H.264
TV System	PAL/NTSC
S/N Ratio	≥50dB
PTZ	
Horizontal Rotation Speed	200°/S
Horizontal Rotation Range	0°~360°
Tilt Rotation Range	0°~90°
Tilt Rotation Speed	100°/s
Auto Flip	Support
Ratio Speed	Support
360 Scan	Support
A-B Scan	Support
Preset Points	220
Guard Tours	3 Groups
Guard Points	Max 16 points
Lens	
Focus Length	3.9mm-85.5mm
Focus Control	22X Optical Zoom
Night Vision	
Infrared LED	ϕ22x8PCS+ϕ16x6PCS
Infrared Distance	120M
Auto Control IR LED	PWM
IR Power On	CDS Auto Control
Network	
Ethernet	Built-in RJ45 network interface, support 10M/100M IP DATA
Protocol	TCP/IP, HTTP, HTTPS, DHCP, RTP, RTSP, RTCP, NTP
Onvif	Support ONVIF 2.4
Streamer	v4.1
General	
Housing	Metal, IP66
Operation Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤90% Non Condensing
Heater & Blower	Auto temperature control
Power	DC12V/4A
Lightning Protection	Transient voltage 6000V
Dimension	32x32x43(cm)
Weight	10.2kgs

\*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.