

Box IP Camera

4 Mega Pixel

EE4MPBX-S



FEATURES

H.264

**4MP
1080P**

1/3" OV High-resolution CMOS Sensor

H.264/H.265/MJPEG/AVI

PoE Support 802.3af

Onvif Compliant

EE4MPBX-S

4MP Box IP | EE5MPBX-S

v1.2-8.17

Camera	
Image Sensor	1/3" OV High-resolution CMOS Sensor
Resolution	4MP
Effective Pixels	2688(H)*1520(V)
Compression	H.264/H.265/MJPEG/AVI
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	≥52dB
Scanning System	Progressive
Lens	
Focus Length	2.7-13.5mm
Focus Control	Manual
Lens Type	C/CS Mount
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP,HTTP,DHCP,RTP,RTSP,RTCP,NTP
Onvif	Support ONVIF 2.4
Streamer	V4.1
POE	internal, Support IEEE 802.3af
Main Stream 1	2560*1440@20fps
Main Stream 2	2304*1296@30fps
Camera Features	
Day/Night	Color/ B&W (IR cut filter with auto switch)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
Defog mode	Support
WDR	Support
Motion Detection	Support
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean,Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands,Ukrainian
Audio	2-way audio 1-ch 3.5 mm audio input interface 1-ch 3.5 mm audio output interface
SD Card Support	Support 64G Micro SD
General	
Housing	Metal
IR Cut Filter	Yes
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 550mA
Dimension	148(W)x79(H)x57(D)mm
Weight	585g
# Software license compatibility codes: FW-STRRSPxx ; ES-STRTSPxx, ES-STRMFULLxx	

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.